



1



2



3



4



5

**STANDARD EQUIPMENT:**

- 3-point linkage cat. II and III with hitch cross shaft
- Supporting leg
- 5 rows of cultivator tines S type 45 x 12 with straight coulter
- Hydraulic working depth adjustment on the main frame, and mechanical (supporting wheels) on the side frames
- Tubular roller Ø 400 mm
- Row of harrow springs behind the roller
- Transport chassis with wheels 10.0/7,5-15,3
- Supporting side wheels 24x8.00-14,5
- Hydraulic folding to transport position
- Mechanical transport lock

**OPTIONAL EQUIPMENT:**

- Front leveling board with mechanical working depth adjustment
- Spring leveling board with mechanical working depth and angle adjustment
- Strengthened cultivator tine type S 45x12 with duck foot coulter
- Two rollers (Ø 275 mm + Ø 310 mm) with harrow springs instead of tubular roller
- Warning plates with LED lights

Ref. No.	Working width /m/	Number of tines /pcs/	Power demand /HP/	Weight /kg/
8510	6,0	55	120	3200
8511	7,0	67	160	3350
8512	8,0	77	200	3500



**zagroda**  
AGRICULTURAL TECHNIQUE

## **Trailed seedbed combination**

**Category: Soil cultivation » Seedbed combinations  
and universal cultivators**

**Product code: 8510 / 8511 / 8512**

Working depth: up to 15 cm

ZAGRODA.EU